



**Jeep Wrangler Premium Replacement Soft Top with or without
Upper Doors - with Tinted Windows
Installation Instructions
For: Jeep Wrangler/TJ 1997 – 2006
Part Number: 14010135**

With factory original equipment hardware add upper door



Installation Tips

Before you begin installing this kit, read all the enclosed instructions

For a smooth fit:

For an easy installation, product should be left out in the sun or where the temperature is above 72 degrees for about 1-2 hours. This will make the material pliable and easier to install.

WEAR SEAT BELTS AT ALL TIME

Table of Contents

Installation Tips..... Page 1
Tools Needed..... Page 1
Part Included..... Page 1
Removal of Top..... Pages 1-2
Installation of Top..... Page 2-6
Care and Maintenance..... Page 7
Warranty..... Page 7

Tools Needed

- Safety Glasses
- Phillips Screwdriver

Parts Included

- Fabric Top: 1 ea.
- Right Quarter Window: 1 ea.
- Left Quarter Window: 1 ea.
- Rear Window: 1 ea.

Requires the following OE Hardware

- Wind Channel
- Door Surround Kit
- Pass/Driver Bar Bracket
- Bow Assembly Kit
- Tailgate Bar



Removal of existing Soft Top

Step 1

Removal of rear quarter windows and rear windows

Remove the both quarter windows and the rear Window. Remove the metal Tailgate Bar from the bottom of the Rear Window and set it aside.



Step 2

Release plastic strip from retainer

Release the plastic strip sewn to the top above the doors. Pull down and out to slip the plastic out of the channel.



Step 3

Release windshield latches

Release the latch that secures the header to the windshield. Pull up on the lever and then down and out to release the hook from the slot in the windshield frame.



Step 4

Release rear corners

Release the rear corners. Pull downward gently and then out to release the plastic strip from the retainer on the vehicle.



Step 5

Release rear bow

Release the fabric from the rear bow and allow the bow to drop onto the tailgate. Unsnap the soft top from the rear of the bow.



Step 6

Center bow release

Undo the Velcro flap around the Center Bow



Step 7

Removal of header assembly from bow assembly

Collapse the bow assembly towards the tailgate. With the bow assembly laying on the tailgate, remove the 8 or 14 screws that fasten the fabric to the header assembly. Make sure to place the set the screws in a secured location as you will be using them in the installing the new top fabric.



Step 8

Now remove your old top towards the rear of the vehicle

Installation of your Premium KING4WD Soft Top

Step 1

Installation of new soft top to header

In order to install the top fabric, make sure that the bow assembly is folded down towards the rear of the vehicle.

Lay the soft top over the roll bar with the underside facing up and with the plastic strip facing up aligned with the front edge of the header. Locate the center hole and install the first screw to secure the soft top. Then proceed to install screws in the remaining seven or thirteen holes along the front of the header.



Step 2

Snap top to rear bow

Raise the header and bow assembly toward the windshield and into position.

Inside the top, snap the 6 snap buttons to the Rear Bow (six snaps).



Step 3

Secure header to windshield

Close the header latches to secure the front of the top to the windshield. Catch the hook in the slot in the windshield frame and then close the lever over it so that it lays flat against the windshield frame.



Step 4

Install rear corner

Make sure that the center bow is centered in the hook and loop flap inside the top.

DO NOT FASTEN FLAP AT THIS TIME.

Pull down gently on the rear bow and work the plastic sewn to the rear on the rear corners of the soft top into the retainer of the vehicle.



Step 5

Fasten center bow assembly

Wrap the hook and loop flap inside the top around the center bow and make sure the Velcro is properly secured.



Step 6

Attach quarter panel zippers

Locate the rear left and right quarter panels. Start the zipper at the front top corner of the quarter panel, next to the door. Close the zipper slider 10" - 12" along the top of the panel allowing the rest of the panel to hang freely for now.



Step 7

Securing front quarter panels

Roll the plastic along the front of the panel surrounding the vehicles door channel.



Step 8

Securing upper door opening

Locate the plastic strip that is sewn into the soft top, there is one on each door, Maneuver the plastic strip into the door channel surrounding the door opening,



Step 9

Securing quarter panels

Completely close the zippers on the quarter panels the rest of the way, moving from front to back. Now roll the belt rail into the vehicles channel starting from the rear and moving towards the front.



Step 10

Install tailgate bar onto rear window

Locate rear window. This can be done by either laying the rear window flat on a table or by holding the rear window and sliding the tailgate bar onto the rear window. The rear bar has a "C" channel shape, insert the bar into the tubed strip that is sewn the backside of the rear window. Be careful not to push too hard when sliding the rear bar into the tubed strip, you can cause damage rendering the rear window useless.



Step 11

Installation of tailgate bar on vehicle

Insert the Tailgate Bar into the mounts on each side of the tailgate opening with the weather stripping towards the outside of the vehicle.



Step 12

Secure rear window flaps

Inside the top locate the flaps sewn to the top on each side of the rear window opening. Pull the flaps over to cover the zipper and tuck them in.



Step 13

To fold the top down

Remove quarter panels and rear window

Remove the quarter panels and the rear window and store them in a clean safe location

Step 14

Release the front of the top from the windshield. Raise the front of the deck and collapse the rear bows, tucking the two plastic strips above the door openings and the stay pad on the rear bow inside of the bows, Wrap the fabric around the bows, then tuck the rear legs of the top under the bows.



When operating the vehicle without the quarter windows, the rear window should be rolled up and secured with the elastic garters for proper ventilation

Care and Maintenance of your New Top

Your top is made of the best materials. To keep it looking new and for the maximum possible wear, it will need. Periodic cleaning and maintenance

Washing your Soft Top: The fabric should be washed often. Using mild soap, warm water and a soft bristle brush. Rinse with clean water to remove all traces of soap.

Zippers: Keeping the zipper cleaned and lubricated with a silicone lubricant will help prevent damage and keep the zippers in smooth working condition. If zipper opens behind the slider, the slider may have been spread apart. The problem can usually be repaired by using an ordinary pair of pliers to bring the sides back into parallel. Return the slider to the end of the zipper in the normal open position. Squeeze lightly at first and test the zipper. If the zipper continues to remain open squeeze more firmly with the pliers and try the zipper again. Repeat this procedure until the zipper operates correctly.

Water: In the event of leaking through the seams, 3M Scotchgard® may be applied on the inside of the seams to stop the leaking. Rips in the fabric may be repaired with iron on repair patches. Iron the patches to the inside of the top, carefully following the Bondex instructions.

Snaps: Keep snaps cleaned and lubricated with silicone to help prevent snaps from sticking to the studs. If a snap does become stuck to stud, use a screwdriver and gently pry apart to prevent the permanent damage to the snap or the top fabric, follow with a light coat silicone.

LIMITED WARRANTY

We warrant our product to be free from defects in material and workmanship, for terms specified below, provided there has been normal use and proper maintenance. This warranty applies to the original purchaser only. All remedies under this warranty are limited to the repair or replacement of any item or items found by the factory to be defective within the time period specified.

If you have a warranty claim, first you must call our customer service department at the number listed below. You must retain proof of purchase and submit a copy with any items returned for warranty work. Upon completion of warranty work, if any, we will return the repaired or replaced item or items to you freight prepaid. Damage to our products caused by accidents, fire, vandalism, negligence, mis-installation, misuse, Acts of God, or by defective parts not manufactured by us, is not covered under this warranty.

THE WARRANTY TIME PERIOD IS AS FOLLOWS: ALL "GOODS" MANUFACTURED BY OUR COMPANY: FOUR YEARS FROM DATE OF PURCHASE. ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE CREATED HEREBY ARE LIMITED IN DURATION TO THE SAME DURATION AND SCOPE AS THE EXPRESS WRITTEN WARRANTY. OUR COMPANY SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE.

Some states do not allow limitations on how long an implied warranty lasts, or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

For further information, please contact: KING4WD for Customer Service.